



## SPECIFICATIONS:

**MODEL   CUBIC METERS   HEIGHT   TONNES   AUGER   DIAMETER   CONE DEG   CONE TO GROUND**

**SILOS**

150	5.5	3.6	4.4	6.0	(19)	1.8	30°	600
300	10.5	4.0	8.7	6.7	(21)	2.4	45°	500
300E	10.5	4.5	8.7	7.2	(23)	2.4	45°	1000
420	15.3	4.8	12.0	8.0	(26)	2.4	45°	500
420E	15.3	5.3	12.0	8.5	(28)	2.4	45°	1000
510	18.5	5.6	14.8	8.8	(29)	2.4	45°	500
510E	18.5	6.1	14.8	9.3	(31)	2.4	45°	1000
750	27.3	5.7	23.0	9.0	(30)	3.0	30°	500
*940	32.7	4.6	27.5	9.0	(30)	3.7	30°	500
*1200	41.4	5.4	35.0	9.8	(32)	3.7	30°	500
*1500	50	6.2	40.0	11.0	(36)	3.7	30°	500
*1700	58.7	7.0	50.0	12.2	(42)	3.7	30°	500
*2000	64	6.0	55.0	11.0	(36)	4.5	30°	500
*2350	77	6.8	65.0	12.2	(42)	4.5	30°	500
*2800	90	7.6	75.0	13.7	(45)	4.5	30°	500
**3600	118	8.7	100.0	16.7	(55)	4.75	30°	550
**3960	132	9.5	110.0	18.3	(60)	4.75	30°	550

**FIELD BINS**

*20T	24.3	3.2	20.0			3.7	30°	AUGER BOOT
*30T	37	4.2 (3.8)	30.0			4.5	30°	AUGER BOOT

**AUGER FIELD BIN**

* 30T	37	4.2 (3.8)	30.0			4.5	30°	AUGER CLEARANCE 4.3 METERS
-------	----	-----------	------	--	--	-----	-----	-------------------------------

**CATTLE & SHEEP FEEDERS**

			<u>WHEAT</u>	<u>OATS</u>	<u>DIAMETER</u>	<u>INVERTED CONE</u>
40 BAGS	4.1	2.4	3.3	2	TROUGH 2.3, ROOF 3.45	45°
*90 BAGS	8.6	2.7	7	4.3	TROUGH 3.1, ROOF 4.15	45°
*250 BAGS	24.7	4.2	20	12.4	TROUGH 3.1, ROOF 4.4	45°

**SHEEP FEEDERS ARE SAME DIMENSION AS CATTLE FEEDERS BUT LOWER TROUGH**

**SUPERPHOSPHATE SILOS**

*36CM	36	5.2	26/40	9	(30)	3.7	40°	550
*44CM	44	6	34/51	9.8	(32)	3.7	40°	550
*53CM	53	6.8	40/60	11	(36)	3.7	40°	550
*80CM	80	7.6	60/92	13.7	(45)	4.5	40°	550
**90CM	90	7.8	69/103	15	(50)	4.75	40°	550

\* ESCORT REQUIRED FOR THESE SILOS \*\* TWO ESCORTS REQUIRED FOR THESE SILOS

\*AUGER BOOT OPTIONAL ON ALL MODELS, EXCLUDING 150- 510E

\*WHEAT DENSITY BASED ON 820KG/CM WITH 5% COMPACTION