

HE SILOS

Storing The Nation's Grain

AUSTRALIAN MADE & FAMILY OWNED

HE Silos Gunnedah, a family business spanning three generations, has been manufacturing grain storage solutions for over half a century. With our wealth of knowledge and experience, we can confidently assist you in your new purchase.

QUALITY

Our skilled staff are equipped to produce top-tier products. We maintain our commitment to quality through a rigorous assurance program, ensuring that each product meets our high standards. All our products are welded, crafted from premium galvanized steel, featuring an all-galvanized base, and zincalume walls and roof. Our silos are engineered to last.

WARRANTY

HE Silos Gunnedah offers necessary repairs or replacements under warranty. We differ from others with our follow up service to ensure your product is operating to your needs. Every product is backed by a 5-year warranty to safeguard consumers.



EFFICIENT ORDER PROCESS

1. You accept your written quote
2. We send all relevant documents for your order including silo design, foundation specs & 20% deposit invoice.
3. You prepare your concrete silo foundation.
4. Our manufacturing team pre fab your silo ready for pick up or delivery.



30 Borthistle Road, Gunnedah NSW 2380

Phone: 1300 764 700

Email: sales@hesilos.com.au

Website: www.hesilos.com.au



Connect with us



**FINANCE
AVAILABLE**
ENQUIRE TODAY

TRANSPORTABLE GRAIN SILOS

GST INCLUSIVE

FEATURES & INCLUSIONS

- Delivered and installed ready to use
- Silos sealed gas tight complying with Australian standard AS2628
- Zincalume barrel and roofs and galvanized support structure
- White Colourbond walls & roof to effectively reduce the temperature inside the silo, ensuring greater storage conditions
- All models can be custom designed to suit your specific needs
- Covered by HE Silos Gunnedah 5 year warranty
- Sight glasses x 2 in top and bottom barrells to indicate level of grain in silo
- HE Silos Phosbox
- Safety ladders and cages that comply with Australian Standard AS1657. Slide ladder that locks into place above ground to prevent accessibility to children and visitors
- Pressure relief valve
- Ground opening lid
- Manhole in base

DELIVERY & INSTALLATION

- Model 150 - 2800
Truck & pilot vehicle
- Model 3600 - 4320
Truck & 2x Pilot Vehicles

OPTIONAL UPGRADE / EXTRAS

- Additional sight glasses
- Sealed Bagging chute
- Colourbond white wall & roof
- 10mm Footplates
- Fumigation & Aeration

Tonnes are approximate based on wheat at 810kg/m³ with 5% compaction

Model	Tonnes	Cubic Meters	Height	Auger	Diameter	Cone Degree	Cone to Ground
150	4.4	5.5	3.3m	6.0m (19')	1.8m	30	600mm
300	8.3	9.8	3.8m	6.7m (21')	2.4m	45	600mm
300E	8.3	9.8	4.5m	7.2m (23')	2.4m	45	1000mm
420	11.4	13.5	4.6m	8.0m (26')	2.4m	45	600mm
420E	11.4	13.5	5.3m	8.5m (28')	2.4m	45	1000mm
510	14.5	17.1	5.5m	8.8m (29')	2.4m	45	600mm
510E	14.5	17.1	6.1m	9.3m (31')	2.4m	45	1000mm
750	23.4	27.6	5.6m	9.0m (30')	3.0m	30	600mm
940	28.0	33.0	5.0m	9.0m (30')	3.7m	30	600mm
1200	35.2	41.5	5.8m	9.8m (32')	3.7m	30	600mm
1500	42.6	50.2	6.7m	11.0m (36')	3.7m	30	600mm
1700	49.8	58.7	7.5m	12.2m (42')	3.7m	30	600mm
2000	53.1	62.5	6.2m	11.0m (36')	4.5m	30	600mm
2350	63.7	75.0	6.9m	12.2m (42')	4.5m	30	600mm
2800	74.2	87.4	7.8m	13.7m (45')	4.5m	30	600mm
3600	97.0	114.2	8.7m	16.7m (55')	4.75m	30	550mm
3960	108.8	128.0	9.5m	18.3m (60')	4.75m	30	550mm
4320	121.0	142.4	10.3m	20.0m (65')	4.75m	30	550mm